

Revolution™

Hunter Engineering Company has combined its technological leadership and innovative style to produce a fully automatic tyre changer completely designed and built in the USA - The Revolution. The Revolution uses the same fully automatic method for all tyre and wheel combinations, saving time on today's diverse assemblies. The fully automatic process also removes the need for a skilled operator by turning all levels of tyre technicians into experts.

Specifications

| SPECIFICATION | |
|------------------------|--|
| Mount / Demount Tool | Polymer Self Inserting Leverless |
| Clamping Type | Centre w/ Quick Clamp |
| Bead Loosening Type | Upper / Lower Roller |
| Match Mounting Capable | YES |
| Rim Diameter Range | 305 mm - 762 mm (12 in. - 30 in) |
| Maximum Tyre Diameter | 1,270 mm (50 in) |
| Maximum Wheel Width | 381 mm (51 in) |
| Drive | Variable up to 15 rpm CW / CCW Torque: 875 ft-lbs (1186 Nm) |



Features

- Fully Automatic, minimal operator intervention
- Space saving spindle wheel lift
- New swift & versatile central clamping system
- Automatic leverless tool & demounting hook
- Automatic TPMS Protection
- Damage free bead loosening rollers
- Powered Press Arm Assist
- Simple Touch screen interface
- Simplifies training - Learn on one tyre and apply skill to all!



For further information or to arrange a 'FREE' no obligation site visit please contact Pro-Align by calling

(UK) 01327 323007

(IRE) 01 5060699

Email:

enquiries@pro-align.co.uk

enquiries@pro-align.ie

Copyright © Pro-Align Ltd / Hunter Engineering Company

Because of continuing technical advancements, specifications, models and options are subject to change without notice.