

TC Line

Sharing similar technology and benefits of the popular and larger Hunter Auto34 system, this small, yet versatile leverless tyre changer brings a robust build quality at a value that makes it stand out from the crowd.



**TC
LINE**

Specifications

SPECIFICATION	
Weight	330Kg (338 Fl)
Voltage	1ph, 200/265v, 50/60Hz
Rim Diameter Range	254mm – 762mm (10 in. – 30 in.)
Maximum Tyre Diameter	1143mm (43in.)
Maximum Wheel Width	381mm (15in.)
Bead break.pow. (each arm)	12000 N
Maximum torque	120 Kgm
Bead breaker movement	Automatic
Drive	1,5 KW inver. + 0,75Kw moto5
Recommended air supply	8 – 10 bar
Power requirements	13AMP. 220v 1ph



Features

- Quick 'Extra- Grip' central clamping
- Dual bead breaker roller system
 - Single motion simultaneous bead positioning
 - Controlled bead breaking
- Automatic Arm Locking
- Expandable base to cater for wheels 254mm – 762mm (10 in. – 30 in.)
- Damage proof leverless tool head

For further information or to arrange a 'FREE' no obligation site visit please contact Pro-Align by calling

(UK) 01327 323007
(IRE) 01 5060699
Email:
enquiries@pro-align.co.uk
enquiries@pro-align.ie

Copyright © Pro-Align Ltd / Hunter Engineering Company
Because of continuing technical advancements, specifications, models and options are subject to change without notice.